

UNWINDER & REWINDER FOR EPSON C7500 PRINTER



LABEL REWINDER (ASD1111-SD) - Epson C7500 printer - LABEL UNWINDER (ASS1111-SD) (<u>Not included</u>) The new Unwind/Rewind System for Epson C7500 Label Printer can handle media up to 127mm wide and unwind/ rewind 250mm OD label rolls. Units are equipped with a 3" or adjustable core holder (40-118mm).

The printer feet fit into notches on the printer plate. This way the correct unwinding / rewinding operations are guaranteed and units are safely aligned with the printer.

An external power supply 100/240 VAC - 2.5A -- at 24V allows an electronic circuit to provide, through the tension arm, the adjustment of the rotation speed and rotation direction. A 2A fuse is used as protection.

The unwinder and rewinder for Epson C7500 printers have two types of speed adjustments: it is possible to set the speed through a knob and the tension arm automatically adjusts the speed from zero up to the desired speed. When the roll runs out, the device stops beeping.



LABEL UNWINDER

The position of the tension arm is calibrated as follows: - When the printer forwards the media for printing, the tension arm goes up, the device unwinds the media.

When the tension arm is in the middle position, the device is idle.
When the printer pulls back the media, the tension arm goes down,

the device rewinds it.

LABEL UNWINDER

ASS1111-S0	40-118mm adjustable core holder
ASS1114-S0	3" fixed core holder



LABEL REWINDER

The position of the tension arm is calibrated as follows:

- When the printer forwards the media for printing, the tension arm goes down, the device rewinds the media.

- When the tension arm is in the middle position, the device is idle.
- When the printer pulls back the media, the tension arm goes up, the device unwinds it.

	LABEL REWINDER	
older	ASD1111-S0	40-118mm adjustable core holder
	ASD1114-S0	3" fixed core holder

A WORLD OF SOLUTIONS THESE PRODUCTS ARE CERTIFIED:

RoHS


FC

CE

SMART SOLUTIONS FOR THE LABELING INDUSTRY

In order to guarantee a neatly aligned media path, a specific baseplate which easily accommodates the Epson C7500 is available.

PRINTER PLATE		
EPS75PL-UW	UW printer plate for EPSON C7500	
EPS75PL-RW	RW printer plate for EPSON C7500	



UW-RW printer plate for Epson C7500

Press roll

Specifics

• 3" Fixed Core Holders

Maximum Label Width 130mm

Maximum Outside Roll Diameter 250mm

Waste matrix removal



INLINE MATRIX REMOVER FOR EPSON C7500 LABEL PRINTER

Designed as an in-line option, the matrix remover for the Epson C7500 is an all-in-one system capable of removing the excess label material around each pre die cut label, and rewinding.

By printing on die cut label rolls with the matrix intact, you can be assured that your labels are completely printed, edge-to-edge. A quick and easy to maximize your printing uptime.

Electronic and mechanical features: an external power supply 100/240VAC - 5A --- at 24V allows an electronic circuit to provide, through the sensor, the adjustment of the rotationspeed. A 2A fuse is used as protection.

INLINE MATRIX REMOVER

EPS75-MTX27

Matrix remover for EPSON C7500



inline matrix remover + epson C7500 printer